

## **Applications:**

\*Used in various vacuum tire

## Features:

\*Makes seating the most difficult bead not only safe but simple, fast and economical

- \*Designed for commercial use on all tires from 4" to 24.5" sizes
- \*Operates in standard shop air. Max 120PSI
- (Picture on the right is found on the internet)



Easy carry handle for portability 1/4" inlet shutoff valve allows for filling correct amount of air

Rust and corrosionresistant powder-coated for durability

Pressure gauge makes it easy to fill with the optimal amount of air

1 1/2 ball valve quickly releases air between bead and rim Handle can be moved  $90^{\circ}$  in vertical direction to open and shut the valve, easier and more ergonomic

Lip on the threaded		
barrel for proper angel		
for air insertion for		
correct bead seating		

Capacity	5 gallon	Capacity
Body Dia.	9.4"	Body Dia.
Total Length	18.5"	Total Length
Inlet Valve	1/4"NPT with plug	Inlet Valve
Outlet Valve	1-1/2" NPT	Outlet Valve
Pressure Gauge	Dia. 2.0" Range 0-200PSI	Pressure Gau
Working Pressure	e 40-120PSI	Working Pres
Safe Pressure	135-150PSI	Safe Pressure
G.W./N.W.	17.6/19.8 lbs	G.W./N.W.
Carton Size	18.9"x15"x9.8"	Carton Size

10 gallon			
12"			
21"			
1/4"NPT with plug			
1-1/2" NPT			
Dia. 2.0" Range 0-200PSI			
Working Pressure 40-120PSI			
135-150PSI			
23.6/26.4 lbs			
21.5"x17.7"x12.4"			



## **JUST IN HARDWARE CO., LTD**

Add:Wuxi, Jiangsu, China / Tainan, Taiwan Tel: +86-510-83897891 Fax: +86-510-83897895 Email: sales2@justinhardware.com www,justinhardware.com www.justinfitting.com